

PRIME MARINE SERVICES, INC.

Model 30 PCPC

The Model 30 Prime Cutter is a hydraulic gated shear used to cut steel pipe {depending on wall thickness} and concrete piles {depending on shape, composition, and rebar}. This tool can be utilized above and below water and be configured to any orientation. The patented design utilizes a hydraulic gate to close around the member you are attempting to cut. This tool can also be configured to crimp steel pipe. See below for openings.



TECHNICAL DATA & SPECIFICATION - MODEL 30 PCPC

Description		Imperial	Metric
Blade Circuit	Max Operating Pressure	4000 psi	276 bar
	Max Operating Flow	75 gpm	189 l/min
Pin Circuit	Max Operating Pressure	2500 psi	172 bar
	Max Operating Flow	20 gpm	76 l/min
Gate Circuit	Max Operating Pressure	2500 psi	172 bar
	Max Operating Flow	20 gpm	76 l/min
Weight	Approximately	16,500 lbs	7,484 kg
Dimensions	Approximately	13' 2" x 6' 8" x 4' 4"	14.01m x 2.03m x 1.32m
Cutter Opening (Wide) 46"		Cutter Opening (Long) 40" 5/8"	

Prime Marine Services, Inc.
 312 S. Bernard Rd. Broussard, LA 70518
 Phone: (337) 837-6500 Toll Free: 877-837-6511
www.primemarineinc.com